



## 1 产品概述

## 2 主要特性

- ❖ MPEG-2 MPEG-4 AVC/H.264
- ❖ MPEG-1 Layer 2 LC-AAC,HE-AAC
- ❖ 2
- ❖ VBR CBR
- ❖ PAL NTSC
- ❖ IP MPTS( ) SPTS( )
- ❖
- ❖ (LCD)
- ❖ NMS/SNMP/Web

## 3 技术指标

输入接口	1 CVBS , 1 SD-SDI
	2 (BNC), 1 ( 2 )(XLR)
	1 ASI(BNC )
视频	PAL:720*576i/352*288i/320*240i/320*180i/

		176*144i/160*120i/160*90i @50Hz
		NTSC:720*480i/352*288i/320*240i/320*180i/
		176*144i/160*120/160*90 @59.94Hz
		MPEG-2 MPEG-4 AVC/H.264
		0.25~15Mbps(H.264)
		0.5~15Mbps(MPEG-2)
		CBR/VBR
	GOP	IPPPP, IBPBP, IBBPB, IBBBP
音频		MPEG1 Layer 2 LC-AAC,HE-AAC
		48KHz
		24 bit
		32Kbps~384Kbps ( )
复用	ASI	
输出	1 2	ASI BNC
	IP MPTS( ) SPTS( ) UDP	10/100M
系统	(LCD)	(SNMP/NMS/Web)
	/	
通用	( x x )	482mm 455mm 44.5mm
		4kg
		0~45 ( ) -20~80 ( )
		AC 110V 10% 50/60Hz or AC 240V 10% 50/60Hz
		17.6W